
## GRABO PLUS HEAVY LIFTING MADE EASY



## **Specifications:**

Model/SKU	GRABO Plus / GRAB220				
Battery	14.8VDC 2600mAh Li-ion				
Rated Power	16W				
Charger Input Voltage	100-240VAC 50/60Hz				
Battery Charging Time	~2hrs				
Non-Stop Running Time (Full Charge)	1.5hrs				
Running Cycles (On Full Charge)	900 ON-OFF cycles of 10 seconds				
Stand-by Mode (Charge Hold)	30 days				
Pump Service Life	100000+ ON-OFF cycles / 800+ hrs continuous				
Rated Air Flow	20 L/min ( 0.7cfm )				
Maximum Vacuum Rate	11.6Psi ( 0.8 Bar, 80 kPa )				
Maximum Lifting Capacity	170kgs ( 375Lbs )				
LxWxH	297 x 181 x 121 mm ( 11.67 x 7.12 x 4.76" )				
Net Weight (With Battery)	1.6 kg (3.2Lbs)				
Working Temperature	0°~60°C ( 32°F~140°F )				
Applicable Surface Type	Peak/valley heights less than 3mm (0.1"), arc less than 5°				

## Lifting Capacity:

Material	Glass	Ceramic Tiles	Metal	Plastic	Wood	Rough Slate	Rough Concrete	Dry wall	
Direction									
Perpendicular Hold	170 kg (375Lbs)	170 kg (375Lbs)	110 kg (242Lbs)	100 kg (220Lbs)	100 kg (220Lbs)	80 kg (176Lbs)	80 kg (176Lbs)	75 kg (165Lbs)	
Parallel Hold	120 kg (265Lbs)	120 kg (265Lbs)	110 kg (242Lbs)	100 kg (220Lbs)	65 kg (143Lbs)	80 kg (176Lbs)	80 kg (176Lbs)	65 kg (143Lbs)	

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on theGRABO.co.uk or contact a Sales Representative for more information.

GRABO UK:

The Mousery, Beeches Road Rawreth, Wickford, Essex SS11 8GH

info@thegrabo.co.uk

www.theGRABO.co.uk

Main Office: +44 (0)1245 961166

Help & Warranty: theGRABO.co.uk/warranty