


Green Pin® Swivel Eye/Eye – GPSEE



- High tensile steel, quenched and tempered.
- Hot dipped galvanised finish.
- Conforms to US Fed. Spec. RR-C-271 type VII class 2.
- Minimum breaking load is 5 times the W.L.L.
- Marked with CE, W.L.L, manufacturers ID, size and traceability code.
- Certs available **2.1** **MTC** **DoC**

G-7713

Product Code	W.L.L. t	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kgs
GPSEE6	0.39	6	87	32	18	19	27	75	0.1
GPSEE8	0.57	8	106	41	21	25	32	90	0.18
GPSEE10	1.02	10	129	51	24	32	38	109	0.32
GPSEE13	1.6	13	164	64	33	38	51	138	0.6

Product Code	W.L.L. t	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kgs
GPSEE16	2.4	16	199	76	40	44	60	167	1.13
GPSEE19	3.3	19	221	89	44	51	67	183	1.82
GPSEE22	4.5	22	257	102	52	57	78	213	2.83
GPSEE25	5.7	25	295	114	59	64	89	245	4.06
GPSEE32	8.2	32	337	143	68	80	94	273	7.43
GPSEE38	20.5	38	501	178	102	102	150	425	20.8