

ETR 200 N Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5-m pendant control
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120 mm

Applications

ETR 200 N lets you work with a bracket from 720 mm up to 1120 mm. Maximum capacity remains unchanged for the entire arm extension so bulky materials can be lifted without the risk of striking against the structures. The low noise level allows working without causing noise harmful to the operator's health and bothersome to others.

TR 225 N Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120 mm

Optional Accessories

- ✓ 3-pushbutton IP65 pendant control 5 m
- ✓ 3-pushbutton IP65 pendant control 30 m - low voltage

Applications

The low noise level allows working without causing noise harmful to the operator's health and bothersome to others.



ETR 200 N

Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø steel rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz	kW	0.75
Motor speed	rpm	1380
Running current	A	7.2
Machine weight	kg	45
SPL in operator's position	dB(A)	<70
Dimensions w/l closed (open)/h	mm	330/770(1170)/520
Packing dimensions w/l/h	mm	350/820/500

TR 225 N

Maximum capacity	kg	200
Av. full load lifting speed min/max	m/min	19
Max. working height	m	30
Ø wire rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz	kW	0.75
Motor speed	rpm	1380
Running current	A	7.2
Machine weight	kg	46
SPL in operator's position	dB(A)	<70
Dimensions w/l closed (open)/h	mm	330/770(1170)/520
Packing dimensions w/l/h	mm	350/820/500