

RGHK2

THE SCAFFOLDER'S KIT RGHK2

The Scaffolder's Kit comes complete with a two point harness and single leg fall arrest lanyard meaning work can take place at an open edge or ungated ladder hatch.

The lanyard comes with a scaffold hook attached which is designed for simple connection to scaffolding and other steel structures.

Kit contains

- / Front & rear D harness (RGH2)
- / Single leg webbing lanyard and shock absorber (RGL1)
- / 17mm steel screwgate karabiner (RGK1)
- / 60mm aluminium double-action scaffold hook with captive eye (RGK11)

EN 362:2004

EN 361:2002

EN 355:2002



* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*



RIDGEGEAR LIMITED

Nelson Street, Leek, Staffordshire, ST13 6BB

+44 (0)1538 384 108

sales@ridgegear.com

ridgegear.com

ITEM SPECIFICATIONS

RGHK2

FRONT & REAR D HARNESS

RGH2

/ Front & rear attachment point

EN 361:2002

Web material: 45mm RIDGE Protect anti-bacterial polyester*
Fittings: High tensile steel alloy
Weight: 1.1kg

SINGLE LEG WEBBING LANYARD AND SHOCK ABSORBER

RGL1

EN 355:2002

Web material: 26mm RIDGE Protect anti-bacterial polyester*
Fittings: 17mm steel screwgate karabiner (RGK1)
60mm aluminium double-action scaffold hook with captive eye (RGK11)
Max arrest force: <6kN
Length(s): 1.4m (up to 140kg user)
1.8m (up to 100kg user) (including connectors)

17MM STEEL SCREWGATE KARABINER

RGK1

EN 362:2004

Material: Steel
Plating: Zinc
Gate opening: 17mm
External length: 107mm
Closure type: Screwgate
MBS: 23kN
Weight: 160g



60MM ALUMINIUM DOUBLE-ACTION SCAFFOLD HOOK WITH CAPTIVE EYE

RGK11

EN 362:2004

Material: Aluminium
Plating: Anodised
Gate opening: 60mm
Eye diameter: 30mm
External length: 248mm
Closure type: Double action
MBS: 23kN
Weight: 480g

