

PROBAT Aluminium Industrial Platform Step



[Representative image of product]

Product Description

The Probat Platform Step Ladder provides maximum stability and is designed for intensive use in the most demanding environments. It is over-tested to 360kg and with the front and rear stiles constructed using large 50mm aluminium scaffold tube. The mammoth 100mm deep treads are secured using Duraclimb spun-rung technology to provide the strongest possible mechanical connection for intensive use.

Features

- Manufactured from 50mm aluminium scaffold tube for maximum rigidity and stability
- Mammoth 100mm deep steps for maximum climbing support
- Extra-strong 390 x 382mm bi-folding platform
- Large integrated metal tool tray with bucket hook
- Featuring tough spun-rung Duraclimb technology for intensive use
- Convex oversized feet ensure maximum ground contact and grip
- Ideal for use on construction sites and facilities maintenance

Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: FR
- Recommended Usage: Intensive

Common Dimensions

- Tread Depth: 100mm
- Distance Between Treads: 250mm
- Storage Depth: 310mm
- Top Platform Tread (LxW): 390 x 382mm
- Handrail Height: 700mm

Packaging Material

- Polywrap & Wooden Battons

Availability & Delivery

- Stock item. Delivery next day.
- (See exceptions, if applicable, overleaf)

PROBAT Aluminium Industrial Platform Step

Product Dimensions

SKU	Treads ²	Platform Height (mm)	Approx. Working Height ¹ (mm)	Closed Height (mm)	Open Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1205-004	4	950	2700	1910	0	690	980	10.8
1205-005	5	1200	2950	2160	0	720	1140	12.4
1205-006	6	1420	3170	2410	0	750	1300	14.5
1205-008	8	1900	3650	2910	0	810	1620	17.0
1205-010	10	2370	4120	3410	0	870	1940	21.5
1205-012	12	2840	4590	3910	0	930	2260	27.5†

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

Ladders set at an angle of ~75° degrees.

† Heavy Item – 2-person lift required.

² Tread count includes the top platform step/top cap tool tray tread.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1205-004	1910	690	310	0.409	12.1
1205-005	2160	720	310	0.482	14.0
1205-006	2410	750	310	0.56	16.4
1205-008	2910	810	310	0.731	19.6
1205-010	3410	870	310	0.92	24.7†
1205-012	3910	930	310	1.127	31.3†

† Heavy Item – 2-person lift required.

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No.534073, VAT Reg. No.GB134144207
 Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.