

THREE-T Aluminium Industrial Scaffold Tower - Single Width



[Representative image of product]

Product Description

Ideal for use in industrial environments, this is a heavy-duty scaffold tower that is built using the 3T method or Through The Trap. Top-level quality components include locking castors, threaded levelling legs, locking brace hooks. Frame Access design, with rungs spaced 232mm apart, removes the need for a separate or built-in ladder frame. Spare parts are available to replace damaged components or if you need to build additional platform heights. Manufactured in the UK, this range of scaffold towers is also available in double-width and a variety of platform sizes, from 2.0m, 2.5m and 3.0m lengths.

Features

- Fully compliant using the 3T or Through The Trap build method
- 50mm scaffold tube construction with a heavy-duty spigot for maximum strength and crimped abuse-resistant joints
- Toe-board and guardrails for additional security
- Large trapdoor for easy access to top platform
- Quick assembly - designed for the professional user
- Rating - Platform 250kg / Structure 750kg
- Also available as a Double Width tower

Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 250kg
- Standard: BS EN 1004:2004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: UK
- Recommended Usage: Intensive

Common Dimensions

- Platform Length: 2000mm
- Platform Width: 700mm
- Distance Between Rungs: 232mm

Packaging Material

- No Packaging

Availability & Delivery

- Non-stock item. Delivery up to 7 days.
(See exceptions, if applicable, overleaf)



THREE-T Aluminium Industrial Scaffold Tower - Single Width

Product Dimensions

SKU	Platform Height ² (mm)	Approx. Working Height ¹ (mm)	Overall Height (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3012-002	2340	4090	3590	n/a x n/a	108.0†
3012-003	2810	4560	4060	4690 x 3460	118.0†
3012-004	3270	5020	4530	4690 x 3460	123.0†
3012-005	3730	5480	4980	4690 x 3460	128.0†
3012-006	4200	5950	5450	4690 x 3460	132.0†
3012-007	4660	6410	5910	4690 x 3460	135.0†
3012-008	5130	6880	6380	4690 x 3460	147.0†
3012-009	5590	7340	6840	5780 x 4550	151.0†
3012-010	6050	7800	7300	5780 x 4550	177.0†
3012-011	6520	8270	7770	5780 x 4550	180.0†

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

² Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.